

D.C. Power Supply



FEATURES

- * Light and Compact Design
- * 0.01% High Regulation
- * Constant Voltage and Constant Current Operation
- * Series or Parallel Operation Function
- * Remote Control for External Programmable
- * Internal Select for Continuous or Dynamic Load
- * Low Ripple and Noise
- * Overload and Reverse Polarity protection
- * Optional European : Jack Type Terminal

GPS-3030DD

SPECIFICATIONS

CONSTANT VOLTAGE OPERATION	Regulation	Line regulation $\leq 0.01\% + 3mV$ Load regulation $\leq 0.01\% + 3mV$ (rating current $\leq 3A$) $\leq 0.01\% + 5mV$ (rating current $> 3A$)
	Ripple & Noise	$\leq 0.5mV_{rms}$ 5Hz ~ 1MHz (rating current $\leq 3A$) $\leq 1mV_{rms}$ 5Hz ~ 1MHz (rating current $> 3A$)
	Recovery Time Temp. Coefficient Output Range	$\leq 100\mu S$ (50% Load change, Minimum load 0.5A) $\leq 300 ppm / ^\circ C$ 0 to rating voltage continuously adjustable
CONSTANT CURRENT OPERATION	Regulation	Line regulation $\leq 0.2\% + 3mA$ Load regulation $\leq 0.2\% + 3mA$
	Ripple Current Output Range	$\leq 3mArms$ 0 to rating current continuously adjustable (Hi / Lo range switchable)
METER	Digital	3 1/2 digits 0.5" LED display 3 1/2 digits 0.39" LED display Accuracy $\pm (0.5\% \text{ of rdg} + 2 \text{ digits})$
INSULATION	Chassis and Terminal Chassis and AC Cord	20M Ω or above (DC 500V) 30M Ω or above (DC 500V)
POWER SOURCE		AC 100V/120V/220V/240V $\pm 10\%$, 50/60Hz
ACCESSORIES		Instruction manual x 1 , Power cord x 1 Test lead GTL-105 x 1 ($\leq 3A$) European test lead GTL-203 x 1
DIMENSIONS		128(W) x 145(H) x 285(D) mm

ORDERING INFORMATION

Model	Output Volts (V)	Output Amps (A)	Weight (kg)
GPS-3030DD 90W D.C. Power Supply	0 ~ 30	0 ~ 3	5